

## TECHNICAL DATA SHEET (TDS)

# GREZZO

ID Product Code 068



Pag | 1

## PROTECTIVE ENHANCER FOR ROUGH SURFACES

Deep enhancer and protective agent for stones with rough finish.

### Product description:

Deep color enhancing and protective agent, used for intensely enhance color of material. GREZZO also increases resistance against penetration of water and oils, on surfaces and handmade objects with rough finish. It lets the stone breath, it penetrates deeply, enhancing the color of the stone and gives an attractive and deep wet look; it does not make any film.

### Chemical characteristics:

Appearance	Liquid
Color	Yellow transparent
Odor	Characteristic
Specific gravity at 20°C (68°F)	1,30±0,02
Hydro-solubility	Not soluble
pH	N.A.
Drying time at 20°C (68°F)	30-60 minutes*
Complete drying time	4 hours*
Shelf life at 20°C (68°F)	24 months in original container

\* indicative values, depending on the nature of the material and environmental conditions

### Instruction for use

Surface must be clean and dry; stains, mildew, crusting must be scraped off otherwise they will be harder to remove after protection. Application can be done by brush, by roller or by spray gun. It is suggested, when possible, to apply the product by brush because it allows the product to penetrate better into the stone. Application of GREZZO by brush, making pressure, will facilitate penetration into frames and cavities. After 30 minutes rub with a clean cloth to remove excess of product.

### Application tools



Cloth



Brush

### Suggestion for use and recommendations:

- Do not dilute the product with water or other solvents because the preparation is ready for use.
- The material to be treated must be completely dry.
- Once treated, the stone must be left to dry for 24 hours to complete polymerization.
- On very absorbent material, or to further enhance color of treated material, it is possible to make a second cross-handed application after three hours from the first.
- In the case of treatments of statues, vases or decorative items, pay close attention to cavities.
- Product for indoor use only.
- Read carefully recommendations printed on label and perform a preliminary test on a small area before actual use.



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.



TDS N°  
**068**

## TECHNICAL DATA SHEET (TDS)

### Application surfaces

Marble, granite, calcareous stones with flamed, semi-polished, lapped or rough finish.

### Coverage

Pag | 2

With 1 liter (1,05 quart) of product, it is possible to treat up to 10 sqm (110 sq.ft.), depending on material finish and porosity.

### Maintenance of the treated surface

For proper maintenance of the treatment we recommend to carry out periodic washing with our LEM-3 neutral detergent, diluted with water according to the amount of dirt to be removed, without using abrasive tools. The treatment has a variable duration, depending on weather condition it is exposed to and wear of the material. If necessary, it is possible to reapply STRONG 2000 above a previous application.

### Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site [www.bellinzoni.com](http://www.bellinzoni.com)

### Packing

Item N°	Packing	Pcs	Size and weight packaging	Carton per pallet (sea transport)
068CGREZZO001	1,00 lt (33,82 fl.oz.)	12	cm 36x27x26 – kg 16,50	24
068CGREZZO005	5,00 lt (1,32 Gal)	3	cm 40x40x20 – kg 20,00	16
068CGREZZO030	25,00 lt (6,60 Gal)	1	cm 40x32Ø – kg 33,00	24

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling. Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

### H.S. Code

32.08.1010

### Trademark and Origin of the good

BELLINZONI® is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product GREZZO is **MADE IN ITALY**.



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.



TDS N°

**068**